

SINGLE HEAD COMPRESS MACHINE






+66 34 854716 to 7

www.yfm.co.th







2RT












MACHINE SPECIFICATION

3RT



4RT



Rail sliding device

Overview Compressor is a product forming machine which uses 2 or more plates of mold, which are pressed by hydraulic system. When the pressure is being transferred to the mold, compound rubber will be forced to fill up the empty space of the mold, and the heat from the mold will cause the rubber to become stable.

Model		YF-HM-100-1H	YF-HM-200-1H	YF-HM-300-1H	YF-HM-400-1H	YF-HM-600-1H	YF-HM-800-1H	YF-HM-1200-1H
Clamping Force	(kN)	1000	2000	3000	4000	6000	8000	12000
Clamping Stroke	(mm)	300	300	350	400	450	400	500
Rapid clamping speed	(mm/s)	≥50	≥50	≥40	≥40	≥50	≥40	≥40
Heating Plate Size	(mm)	500 x 500	550 x 600	650 x 700	850 x 1000	1000 x 1200	1000 x 1200	1150 x 1400
Heating Plate Spacing	(mm)	200~400	180~480	300~500	300~500	300~500	300~500	400~600
Max Temperature	(°C)	250	250	250	250	250	250	250
Max ejector force	(kN)	60	60	60	120	120	120	-
Motor Power	(kW)	4	5.5	7.5	7.5	7.5 + 4	7.5 + 7.5	18.5 + 18.5
Heating Power	(kW)	13.8	18.3	23.7	39.6	61.8	61.8	68
Machine Dimension	(mm)	2100L 1790W 1775H	2350L 1900W 2100H	2700L 2100W 2400H	3800L 2650W 2650H	4300L 2800W 3200H	4350L 1950W 3700H	6200L 4800W 4000H
Oil Tank Capacity	(L)	250	300	400	540	540	580	2000

**The Above Specification is our Standard Specification.

***For Special Specification/ Dimension, Please contact our personnels.

YFM YONG FONG MACHINERY CO., LTD.

38/5 Moo 1 Leabkhlongmuenprarom Rd., Nadee, Aumpermuang Samutsakorn, Samutsakorn 74000.Thailand
Tel : +66 34 854716 to 7, +66 34 466282 to 3 Fax : +66 34 854718, +66 34 466345 yfmsales@gmail.com www.yfm.co.th