




SINGLE HEAD VULCANIZING COMPRESS











+66 34 854716 to 7

www.yfm.co.th






2RT

MACHINE SPECIFICATION

3RT**4RT**

Rail sliding device



Overview

Vacalizing Compressor is a product forming machine which uses 2 or more plates of mold, which are pressed by hydraulic system and vacuum system will decrease air in the rubber. When the pressure is being transferred to the mold, compound rubber will be forced to fill up the empty space of the mold, and the heat from the mold will cause rubber to become stable.

Model		YF-VC-100-1H	YF-VC-200-1H	YF-VC-250-1H	YF-VC-400-1H
Clamping Force	(kN)	1000	2000	2500	4000
Clamping Stroke	(mm)	300	250	300	400
Rapid clamping speed	(mm/s)	≥50	≥50	≥50	≥40
Heating Plate Size	(mm)	450 x 450	505 x 510	540 x 600	800 x 950
Heating Plate Spacing	(mm)	300 ~ 400	200 ~ 400	300 ~ 400	250 ~ 500
Max Temperature	(°C)	250	250	250	250
Vacuum Cover Stroke	(mm)	200	250	250	350
Max Mould Thickness	(mm)	190	240	240	340
Ejector Stroke	(mm)	250	300	300	400
Max Ejector Force	(kN)	50	60	60	120
Motor Power	(kW)	5.5	5.5	7.5	7.5
Heating Power	(kW)	12	14.7	18.3	42
Machine Dimension	(mm)	1950W 2270L 2650H	2050W 2470L 2940H	2100W 2550L 2900H	2550W 3800L 3850H
Oil Tank Capacity	(L)	250	250	400	400

**The Above Specification is our Standard Specification.

***For Special Specification/ Dimension, Please contact our personnels.

YFM YONG FONG MACHINERY CO., LTD.

38/5 Moo 1 Leabkhlongmuenprarom Rd., Nadee, Aumpermuang Samutsakorn, Samutsakorn 74000.Thailand
Tel : +66 34 854716 to 7, +66 34 466282 to 3 Fax : +66 34 854718, +66 34 466345 yfmsales@gmail.com www.yfm.co.th